


CASSIDA GREASE EPS Series

Product Information

Synthetic extreme pressure greases for food and beverage processing equipment



CASSIDA GREASE EPS 00, 1 and 2 are high performance extreme pressure lubricants specially developed for the grease lubrication of machinery in the food and beverage processing and packaging industry.

They are based on an aluminium complex thickener, synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food and beverage industry.

Certified by NSF for ISO 21469 and registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to Bremer & Leguil Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

CERTIFICATIONS AND SPECIFICATIONS

- NSF H1
- NSF ISO 21469
- Kosher
- Halal



PERFORMANCE FEATURES

- Noted for their long life
- Excellent water resistance
- Excellent oxidation and mechanical stability
- Excellent corrosion prevention characteristics
- Excellent adhesive properties
- Neutral odour and taste

OPERATING TEMPERATURES

EPS 00: -45 °C to +100 °C (peak up to +120 °C)

EPS 1: -40 °C to +120 °C (peak up to +140 °C)

EPS 2: -35 °C to +120 °C (peak up to +140 °C)

APPLICATIONS

CASSIDA GREASE EPS 00

- Enclosed industrial gearboxes
- Automatic, centralised lubrication systems

CASSIDA GREASE EPS 1

- Plain and rolling element bearings
- Enclosed industrial gearboxes
- Automatic, centralised lubrication systems

CASSIDA GREASE EPS 2

- Rolling element and plain bearings
- Joints, linkages and slides
- Recommended for a wide range of applications

CASSIDA GREASES EPS may also be used as protective anti-rust films and as release agents on gaskets and seals of tank closures.

SEAL AND PAINT COMPATIBILITY

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

HANDLING AND STORAGE

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend that the product be used within 3 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 3 years of date of manufacture, whichever is the sooner).

TYPICAL CHARACTERISTICS (Typical for current production. Variations in these characteristics may occur.)

		CASSIDA GREASE EPS		
		00	1	2
Property	Test Method			
NSF Reg. No.		144875	144876	144877
Appearance		White semi-fluid	White smooth paste	
Type of thickener		Aluminium complex		
Worked penetration at +25 °C $\frac{1}{10}$ mm	ISO 2137	400-430	310-340	265-295
NLGI number	DIN 51818	00	1	2
Kin. Visc. (base oil) at +40 °C mm ² /s	ISO 3104	220		
Kin. Visc. (base oil) at +100 °C mm ² /s	ISO 3104	25		
Dropping Point °C	ISO 2176	>200	>240	>240
Classification DIN	DIN 51502	GP HC 00 G-40	KP HC 1 K-40	KP HC 2 K-30
Classification ISO	ISO 6743-9	L-XEBEB 00	L-XDCEB 1	L-XCCEB 2



Bremer & Leguil GmbH
 Am Burgacker 30 - 42
 47051 Duisburg / Germany
 Tel. +49 (0) 203 9923-0
 Fax +49 (0) 203 259-01
www.bremer-leguil.de