

601(E)



CHAIN DRIVE PIN & BUSHING LUBRICANT

Description

Chesterton® 601(E) Chain Drive Pin & Bushing Lubricant is and has been the premium quality light lubricant of choice in industry for over thirty years.

This superior lubricant was specially formulated to penetrate between the close clearance of chain drive bushings and pins to provide critical lubrication. After penetrating close metal to metal tolerances, 601(E) Chain Drive Pin & Bushing Lubricant provides a long lasting, nondrying film which effectively lubricates metal surfaces so they run smoothly with far less wear.

Applications for 601(E) Chain Drive Pin & Bushing Lubricant can be found in every industry in both the production and maintenance areas. Use on any chain drive for assembly lines, conveyers, packaging equipment, hoist chains, link and roller assemblies, forklift trucks, tractors, machinery, chain saws and for any application requiring a high grade light oil. Used on robotic equipment, the product works extremely well both as a lubricant and as an anti-slag coating, allowing easy removal of excess weld spatter

Composition

Chesterton 601(E) Chain Drive Pin & Bushing Lubricant is not simply an oil but an oil formulated with selective compounds to effectively penetrate and lubricate chain drive pins and bushings. The pins, usually starved for oil, take on a new life.

The high quality petroleum base stock contains a uniquely effective additive package which enhances the performance of the product well beyond that of conventional chain lubricants.

Typical Physical Properties

| | |
|---|---------------------------------|
| Appearance | Clear, Amber Liquid |
| ISO VG (ASTM D2422, DIN 51 519) | 22 |
| Specific Gravity | 0,9 |
| Viscosity (ASTM D 445, DIN 51 561) | |
| 40°C (104°F) cSt (mm²/s) | 22 |
| 100° C (212°F) cSt (mm²/s) | 4 |
| Four Ball Wear Test (ASTM D 2266, DIN 51 350) | |
| 40 kg, 1 hr, 75°C, 1200 RPM | |
| Scar Diameter | 0,5 mm |
| Weld Load | 1568 N, 160 kg |
| Flash Point (ASTM D 93, DIN 51 755) | 144°C (291,2°F) |
| Pour Point (ASTM D 97, DIN 51 755) | -25°C (-13°F) |
| Operating Temperature | -23°C to 150°C (-10°F to 300°F) |
| Pin & Vee Block (ASTM D 3233) | |
| Failure Load, Max | 7367 N, 750 kg |
| Torque | 3,2 N.m |
| Coefficient of Friction | 0,06 |

■ **Extreme pressure additives** in the product increase load carrying ability by 300% which is especially needed to meet start-up stresses.

■ **Detergents** prevent dirt and dust from building up on the inside and outside of chains.

■ **Anti-Oxidants** help prevent the build-up of sticky lubricant residues common in other petroleum based lubricants.

■ **Corrosion inhibitors** protect metal against corrosion that would otherwise ruin bearing surfaces, increasing wear and the energy requirements needed to move the chains.

Features

- Rapid Penetration
- Excellent Hydrodynamic Lubrication
- Noticeably Extends Chain Life
- NSF H2 - Registration number 156678 (bulk) and 156049 (aerosol)

Directions

Apply by spraying or using squirt oiler or oil can with extended spout. Apply at each bushing. Apply evenly and reapply as needed. 601(E) can be dispensed in convenient automatic lubrication equipment. Use with Chesterton® 715 Spraflex®/Spraflex® Gold where an extreme pressure surface lubricant is required to protect against water and corrosion and lubricate rollers and drive gear surfaces.

Safety

Before using product, review the Material Safety Data Sheet (MSDS) or the appropriate safety sheet in your area.

Technical Data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W.CHESTERTON COMPANY DISCLAIMS ALL WARRANTIES EXPRESSED, OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE OR USE. LIABILITY, IF ANY, IS LIMITED TO PRODUCT REPLACEMENT ONLY.



Chesterton International GmbH
Am Lenzenfleck 23, DE-85737 Ismaning, Germany
Tel +49-5223-96276-0
www.chesterton.com eu-pds@chesterton.com
© 2018 A.W. Chesterton Company
® Registered trademark owned and licensed by
A.W. Chesterton Company in USA and other countries,
unless otherwise noted.

DISTRIBUTED BY: