

**SAFETY DATA SHEET**

SDS: 4025

**4025 H1 QUINPLEX® FOOD MACHINERY
LUBRICANT**

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

**Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE
COMPANY/UNDERTAKING****1.1. Product Identifier**

Product Name 4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant

Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet**Importer**

Master Fluid Solutions
501 W. Boundary Street
Perrysburg, OH 43551
USA
+1 419-874-7902

Manufacturer

Lubrication Engineers Inc.
1919 E. Tulsa
Wichita, KS 67216
USA
800-537-7683

For further information, please contact

techsupport@le-inc.net

1.4. Emergency telephone number

Emergency Telephone CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Chronic aquatic toxicity	Category 3 - (H412)
--------------------------	---------------------

2.2. Label Elements

Product Identifier

Signal word

None

Hazard Statements

H412 - Harmful to aquatic life with long lasting effects

2.3. Other Hazards

Other hazards

Harmful to aquatic life

No information available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Chemical name	EC-No	CAS No.	Weight-%	Classification (Reg. 1272/2008)	REACH Registration Number
White Mineral Oil	Present	8042-47-5	40 - 50	No data available	01-2119487078-27-0089
Disodium pyrophosphate	Present	7758-16-9	1 - 5	No data available	no data available
Zinc oxide	Present	1314-13-2	1 - 5	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	no data available
Butylated Hydroxy Toluene	Present	128-37-0	0.1 - 1	No data available	no data available
Diphenylamine	Present	122-39-4	< 0.1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) STOT RE 2 (H373) Acute Tox. 3 (H331) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	no data available

The producer of "4025" declares that it contains less than 3% DMSO extractable material by IP-346

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice

If symptoms develop move victim to fresh air. Show this safety data sheet to the doctor in attendance. Do not breathe dust/fume/gas/mist/vapors/spray.

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

Inhalation	Move to fresh air. If symptoms persist, call a physician.
Skin Contact	Consult a physician if necessary. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. Call a physician if irritation persists.
Ingestion	Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Protection of First-aiders	Use personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, Carbon dioxide (CO ₂), Foam, Dry chemical
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.
Flash Point	215 °C / 419 °F

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment.

6.2. Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

6.3. Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Take up mechanically, placing in appropriate

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

containers for disposal. Clean contaminated surface thoroughly.

6.4. Reference to other sections

See Section 12 for more information.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Prevent vapor buildup by providing adequate ventilation during and after use. Do not eat, drink or smoke when using this product.

Hygiene Measures

When using, do not eat, drink or smoke. Remove and wash contaminated clothing before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Material Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational Exposure limits

Chemical name	European Union	The United Kingdom	France	Spain	Germany
White Mineral Oil 8042-47-5	-	-	-	TWA 5 mg/m ³ STEL 10 mg/m ³	AGW 5 mg/m ³
Zinc oxide 1314-13-2	-	-	TWA 5 mg/m ³ TWA 10 mg/m ³	TWA 2 mg/m ³ STEL 10 mg/m ³	-
Butylated Hydroxy Toluene 128-37-0	-	STEL 30 mg/m ³ TWA 10 mg/m ³	TWA 10 mg/m ³	TWA 10 mg/m ³	AGW 10 mg/m ³
Diphenylamine 122-39-4	-	STEL 20 mg/m ³ TWA 10 mg/m ³	TWA 10 mg/m ³	TWA 10 mg/m ³	AGW 5 mg/m ³ H*
Chemical name	Italy	Portugal	The Netherlands	Finland	Denmark
White Mineral Oil 8042-47-5	-	TWA 5 mg/m ³ STEL 10 mg/m ³	TWA 5 mg/m ³	TWA 5 mg/m ³	TWA 1 mg/m ³
Zinc oxide 1314-13-2	-	TWA 2 mg/m ³ STEL 10 mg/m ³	-	TWA 2 mg/m ³ STEL 10 mg/m ³	TWA 4 mg/m ³
Butylated Hydroxy Toluene 128-37-0	-	TWA 2 mg/m ³ C(A4)	-	TWA 10 mg/m ³ STEL 20 mg/m ³	TWA 10 mg/m ³
Diphenylamine 122-39-4	-	TWA 10 mg/m ³ C(A4)	-	TWA 5 mg/m ³ STEL 10 mg/m ³	TWA 5 mg/m ³
Chemical name	Austria	Switzerland	Poland	Norway	Ireland
White Mineral Oil 8042-47-5	-	SS-C** TWA 5 mg/m ³	TWA 5 mg/m ³	TWA 1 mg/m ³ STEL 2 mg/m ³	TWA 5 ppm STEL 15 ppm
Zinc oxide 1314-13-2	TWA 5 mg/m ³	TWA 3 mg/m ³ STEL 3 mg/m ³	TWA 5 mg/m ³ STEL 10 mg/m ³	TWA 5 mg/m ³ STEL 10 mg/m ³	TWA 2 mg/m ³ STEL 10 mg/m ³
Butylated Hydroxy Toluene 128-37-0	TWA 10 mg/m ³	SS-C** TWA 10 mg/m ³	-	-	TWA 10 mg/m ³ STEL 30 mg/m ³

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

		C1 STEL 40 mg/m ³			
Diphenylamine 122-39-4	H* STEL 1.4 ppm STEL 10 mg/m ³ TWA 0.7 ppm TWA 5 mg/m ³	SS-C** H* TWA 10 mg/m ³	-	TWA 5 mg/m ³ STEL 10 mg/m ³	TWA 10 mg/m ³ STEL 20 mg/m ³
Chemical name	Hungary	Belgium	Czech Republic	Greece	Sweden
White Mineral Oil 8042-47-5	Rákkeltó hatású Ceiling 5mg/m ³	TWA 5 mg/m ³ STEL 10 mg/m ³	TWA 5 mg/m ³ Ceiling 10 mg/m ³	TWA 5 mg/m ³	LLV 1 mg/m ³ Indicative STLV 3 mg/m ³
Disodium pyrophosphate 7758-16-9	-	TWA 5 mg/m ³	-	-	-
Zinc oxide 1314-13-2	STEL 20mg/m ³ TWA 5mg/m ³	TWA 10 mg/m ³ TWA 5 mg/m ³ STEL 10 mg/m ³	TWA 2 mg/m ³ Ceiling 5 mg/m ³	TWA 5 mg/m ³ STEL 10 mg/m ³	LLV 5 mg/m ³
Butylated Hydroxy Toluene 128-37-0	-	TWA 2 mg/m ³	-	TWA 10 mg/m ³	-
Diphenylamine 122-39-4	-	TWA 10 mg/m ³	TWA 10 mg/m ³ Ceiling 20 mg/m ³ Chronické účinky** S*	TWA 10 mg/m ³ STEL 20 mg/m ³	LLV 4 mg/m ³ Indicative STLV 12 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/Face Protection Tightly fitting safety goggles.
Hand Protection Protective gloves.
Skin and Body Protection Long sleeved clothing.
Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental Exposure Controls Do not allow material to contaminate ground water system.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Paste
appearance white
Odor Hydrocarbon-like
Odor threshold No information available

Property **Values**
pH 6 - 8
Melting Point / Freezing Point No data available
Boiling point / boiling range No data available
Flash Point 215 °C / 419 °F
Evaporation rate No data available
Flammability (solid, gas) No data available

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

Vapor pressure	No data available
Vapor Density	< 1 (Air = 1)
Specific Gravity	0.95
Water solubility	negligible
Partition coefficient: n-octanol/water	No data available
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Viscosity, kinematic	not applicable
Explosive properties	No data available
Oxidizing Properties	No data available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

Explosion Data

Sensitivity to Mechanical Impact Not impact sensitive.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

10.3. Possibility of hazardous reactions

Hazardous reactions None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity

Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

The producer of "4025" declares that it contains less than 3% DMSO extractable material by IP-346

Inhalation	May cause irritation of respiratory tract.
Eye Contact	Contact with eyes may cause irritation.

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

**Skin Contact
Ingestion**

May cause irritation.
There is no data available for this product.

Unknown Acute Toxicity

50.19% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 24,106.00 mg/kg

Component Information

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
White Mineral Oil	> 5000 mg/kg (Rat) > 24 g/kg (Rat)	-	= 2062 ppm (Rat) 4 h
Disodium pyrophosphate	= 1800 mg/kg (Rat)	-	> 0.58 mg/L (Rat) 4 h
Zinc oxide	> 5000 mg/kg (Rat)	-	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	> 5000 mg/kg (Rat)	-	-
Butylated Hydroxy Toluene	> 2930 mg/kg (Rat)	> 2000 mg/kg (Rat)	-
Diphenylamine	= 1120 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Skin corrosion/irritation

No information available.

Serious eye damage/eye irritation

No information available.

Sensitization

No information available.

Mutagenic Effects

No information available.

Carcinogenic Effects

No information available

Reproductive toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Target Organ Effects

Respiratory system, Eyes, Skin.

Aspiration Hazard

No information available.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity**Ecotoxicity**

Toxic to aquatic life with long lasting effects Harmful to aquatic life with long lasting effects
Harmful to aquatic life

Chemical name	Algae/aquatic plants	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
White Mineral Oil	-	LC50> 10000 mg/L Lepomis macrochirus 96 h	-
Butylated Hydroxy Toluene	EC50 = 6 mg/L 72 h EC50 > 0.42	-	-

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

	mg/L 72 h		
Diphenylamine	EC50 = 1.5 mg/L 72 h	LC50 3.47 - 4.14 mg/L Pimephales promelas 96 h	EC50 1.69 - 2.46 mg/L 48 h

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available

Chemical name	Log Pow
White Mineral Oil	>6
Butylated Hydroxy Toluene	4.17
Diphenylamine	3.4

12.4. Mobility in soil**Mobility in soil** No information available.**Mobility** The product is insoluble and floats on water.**12.5. Results of PBT and vPvB assessment**

No information available.

12.6. Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste.

Contaminated Packaging Do not re-use empty containers. Empty containers should be taken to an approved waste handling site for recycling or disposal.

OTHER INFORMATION According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

Section 14: TRANSPORT INFORMATION

IMDG Not regulated

ADR/RID Not regulated

ICAO/IATA Not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Water hazard class (WGK) 3

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Not determined
ENCS	Not determined
IECSC	Not determined
KECL	Not determined
PICCS	Not determined
AICS	Not determined

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment No information available

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed
 H311 - Toxic in contact with skin
 H373 - May cause damage to organs through prolonged or repeated exposure if inhaled
 H331 - Toxic if inhaled
 H400 - Very toxic to aquatic life
 H410 - Very toxic to aquatic life with long lasting effects

Issuing Date 04-24-2012

Revision Date 02-15-2019

Reason for revision General Information.

SDS: 4025

4025 H1 QUINPLEX® FOOD MACHINERY LUBRICANT

Issuing Date 04-24-2012

Revision Date 02-15-2019

Revision Number 2.1

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SDS is available at www.LElubricants.com

End of Safety Data Sheet