

# LOGREASE 2

Version 28.07.2009

T  
E  
C  
H  
N  
I  
C  
A  
L  
  
D  
A  
T  
A  
  
S  
H  
E  
E  
T

## DESCRIPTION

**LOGREASE 2** is a multipurpose extreme pressure grease having a high stability to mechanical shear, along with a good resistance to water.  
**LOGREASE 2** stays supple at low temperatures and has a very good resistance to shocks and higher loads.  
**LOGREASE 2** has a well balanced additive package which includes anti-corrosion and anti-oxidation compounds.

## TYPICAL APPLICATIONS

**LOGREASE 2** is well adapted for the lubrication of all types of bearings and articulation which may be submitted to divers conditions.  
**LOGREASE 2** is well suited for centralized lubrication systems that are designed to use NLGI grade 2 grease.

## TECHNICAL CHARACTERISTICS

PROPERTIES	VALUES	UNITS	STANDARDS
Nature of base oil	Mineral		
Thickener	Lithium		
Colour	Brown		
NLGI grade	2		
Worked penetration	265 / 295	x 0.1 mm	NF T 60 - 132
Drop point	180	°C	NF T 60 - 102
Service temperatures	- 30 to + 130	°C	
Test 4 balls			
Load to weld	3090	N	
Load to score	1240	N	