

### 1. Product Description (Benefits)

- ✓ Excellent anti-wear and high load-carrying capacity
- ✓ Enhanced rust and corrosion protection
- ✓ Good oxidation stability and adhesiveness
- ✓ Wide service temperature (-20 °C ~ 150 °C)
- ✓ Mineral oil + Lithium Complex, Yellow

### 2. Application Part

- ✓ Automatic grease lubricator
- ✓ Machine part requiring anti-wear load carrying capacity
- ✓ Bearing under extreme pressure
- ✓ Wheel bearing in steel manufacturing machine

### 3. Product Data

Test item	Test method	Result
Base oil Kinematic Viscosity, 40°C m <sup>2</sup> /S	KS M 2014	220
Worked Penetration 0.1mm	ASTM D 217	280
Dropping Point °C	ASTM D 566	230
Oil Separation wt. %	KS M 2050	2.5
Copper Corrosion grade	ASTM D 4048	1A
Worked Stability 0.1mm	KS M 2049	350
4-Ball EP kg	ASTM D 2596	500

Note : The above data constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field test with the product selected for a specific application

### 4. Suggestion of Using

- ✓ Spatula, brush, lever grease guns and automatic lubricating systems

※ Storage : Approx. 12 months if the product is stored in the original closed container in a dry place